



Ground Floor Extract Air Fans									
Item No.	QTY	Description	Size Ø	Airflow (l/s)	Static Pressure (Pa)	Speed (RPM)	Phase	Motor Size (W)	Accessories
EAFF-01	1	Expelair PX6 Ceiling Extract Fan	200 mm	68	10 Pa		1	35 W	TBC

Block H Ground Floor In-Ceiling Fan Coil Units					
Item No	QTY	Description	Supply Air (l/s)	Cooling Capacity (kW)	Input Power (V/PH/Hz)
I.U.H.0.1	1	Concealed ceiling mounted	87 l/s	3.0 kW	230/1/50
I.U.H.0.2	1	Concealed ceiling mounted	87 l/s	3.0 kW	230/1/50
I.U.H.0.3	1	Concealed ceiling mounted	87 l/s	3.0 kW	230/1/50
I.U.H.0.4	1	Concealed ceiling mounted	140 l/s	4.8 kW	230/1/50
I.U.H.0.5	1	Concealed ceiling mounted	87 l/s	3.0 kW	230/1/50
I.U.H.0.6	1	Concealed ceiling mounted	140 l/s	4.8 kW	230/1/50
I.U.H.0.7	1	Concealed ceiling mounted	87 l/s	3.0 kW	230/1/50
I.U.H.0.8	1	Concealed ceiling mounted	175 l/s	6.8 kW	230/1/50
I.U.H.0.9	1	Concealed ceiling mounted	140 l/s	4.8 kW	230/1/50
I.U.H.0.10	1	Concealed ceiling mounted	87 l/s	3.0 kW	230/1/50
I.U.H.0.11	1	Concealed ceiling mounted	140 l/s	4.8 kW	230/1/50
I.U.H.0.12	1	Concealed ceiling mounted	140 l/s	4.8 kW	230/1/50
I.U.H.0.13	1	Concealed ceiling mounted	87 l/s	3.0 kW	230/1/50
I.U.H.0.14	1	Concealed ceiling mounted	175 l/s	6.8 kW	230/1/50
I.U.H.0.15	1	Concealed ceiling mounted	87 l/s	3.0 kW	230/1/50
I.U.H.0.16	1	Concealed ceiling mounted	87 l/s	3.0 kW	230/1/50
I.U.H.0.17	1	Concealed ceiling mounted	87 l/s	3.0 kW	230/1/50
I.U.H.0.18	1	Concealed ceiling mounted	140 l/s	4.8 kW	230/1/50
I.U.H.0.19	1	Concealed ceiling mounted	175 l/s	6.8 kW	230/1/50
I.U.H.0.20	1	Concealed ceiling mounted	87 l/s	3.0 kW	230/1/50
I.U.H.0.21	1	Concealed ceiling mounted	87 l/s	3.0 kW	230/1/50
I.U.H.0.22	1	Concealed ceiling mounted	175 l/s	6.8 kW	230/1/50
I.U.H.0.23	1	Concealed ceiling mounted	175 l/s	6.8 kW	230/1/50
I.U.H.0.24	1	Concealed ceiling mounted	175 l/s	6.8 kW	230/1/50
I.U.H.0.25	1	Concealed ceiling mounted	87 l/s	3.0 kW	230/1/50
I.U.H.0.26	1	Concealed ceiling mounted	87 l/s	3.0 kW	230/1/50
I.U.H.0.27	1	Concealed ceiling mounted	140 l/s	4.8 kW	230/1/50
I.U.H.0.28	1	Concealed ceiling mounted	175 l/s	6.8 kW	230/1/50
I.U.H.0.29	1	Concealed ceiling mounted	87 l/s	3.0 kW	230/1/50

- 2.1. ALL OPENINGS TO BE 100mm BIGGER THAN DUCT SIZES SHOWN AND TO BE MADE GOOD AFTER DUCTING HAS BEEN INSTALLED - BY BUILDER.
- 2.2. ALL OPENINGS TO BE 50mm BIGGER THAN GRILLE SIZES WHICH INCLUDES A 20mm THICK TIMBER FRAME ALL ROUND OPENING - BY BUILDER.
- 2.3. SLEEVES IN WALLS, IN SLABS AND BEAMS FOR REFRIGERANT PIPES AND DRAINS TO BE MADE GOOD AFTER SERVICES HAVE BEEN INSTALLED - BY BUILDER.
- 2.4. ALL PLANTROOMS TO HAVE FLOOR DRAIN AND WATER POINT.

- 2.1. ALL OPENINGS TO BE 100mm BIGGER THAN DUCT SIZES SHOWN AND TO BE MADE GOOD AFTER DUCTING HAS BEEN INSTALLED - BY BUILDER.
- 2.2. ALL OPENINGS TO BE 50mm BIGGER THAN GRILLE SIZES WHICH INCLUDES A 20mm THICK TIMBER FRAME ALL ROUND OPENING - BY BUILDER.
- 2.3. SLEEVES IN WALLS, IN SLABS AND BEAMS FOR REFRIGERANT PIPES AND DRAINS TO BE MADE GOOD AFTER SERVICES HAVE BEEN INSTALLED - BY BUILDER.
- 2.4. ALL PLANTROOMS TO HAVE FLOOR DRAIN AND WATER POINT.

HO-01-PT-lehae-H-00	2021/03/18	65
---------------------	------------	----