

Front Office Sleighbase Chair

Code: CHAIR-07-TPS-S-X (where X = Fabric)



Back: Min 13mm laminated plywood with 20kg/cm3 foam. SABs 640-1976 complaint.

Arm rest from PVC cappings as integral part of frame. Capping removable by M6 T nuts for replacement.

Seat: Min 13mm laminated plywood with 50kg/cm3 foam with 250/280 neutons hardness factor.

Machine bent frame from tubular construction using 24.5mm diameter by 2.5mm wall thickness tubing.

PVC or molded nylon Tube caps to prevent scratching of floors.

TPS / Enforcement
Sleighbase Chair

CODE Description

CHAIR	TPS	05	S	X
CATEGORY	CATALOG NO	TYPE	FABRIC FINISH	

Barcode:

SARS issued barcode to be fixed underneath metal base plate before delivery to site.

FABRIC OPTIONS (Chair Backrest ONLY)



SUPPLIER: Weavers World

- 8) Laugh - Holly Bush (1471)
- 9) Laugh - Ivory Stones (1469)
- 10) Laugh - Organic Green (1474)

Seat Fabric: Vulcan Black

<http://www.weaversworld.co.za>

Fabric label:

Fabric label
stitched to chair
indicating:
*Manufacturer
*Address
*Contact no.
*e-mail address



TECHNICAL DATA

Backrest:	Backrest (MidBack) to be covered with polyurethane 20kg/cm3 foam SABs 640-1976 complaint foam with min thickness of 50mm to backrest shell. Outer backrest shell to be covered in a 15mm thick layer of low density peeling foam stapled to the periphery of the shell. 480w x 600h, 500h from seat.
Seat:	Seat base to be covered with polyurethane foam with a minimum thickness of 70mm glued to the nylon or suitable alternative material base shell. 50kg/cm3 foam with 250/280 neutons hardness factor. 460w x 480d x 480h.
Arms:	Armrest frame is an integral part of the chairs rolled steel frame makeup. The arm rest is covered with a molded nylon or PVC "capping" which is removable via M6 into M6 T nut assembly fastening screws for replacement if damaged. 650 above FFL
Frame:	Min 80 micron black epoxy powder coated 24.5mm diameter mild steel frame - CNC machine bent and rolled. Frame to support a minimum weight of 130kg.
Supplier:	Embroidered fabric label fixed to side of backrest stating: Supplier, physical address and contact details.
Warranty & Design:	Unit to be supplied with MINIMUM 5 year Warranty under normal office usage conditions. The specifications as contained in this document are the minimum SARS requirements. Vendor to take design responsibility & ensure correct specifications