

- A) THIS DRAWING IS TO BE USED FOR ELECTRICAL PURPOSES ONLY.
- B) DO NOT SCALE THIS DRAWING.
- C) REFER TO ARCHITECTS AND STRUCTURAL ENGINEERS DRAWING FOR ALL BUILDING DIMENSIONS, LATEST BUILDING REVISIONS AND SERVICES.
- D) THIS DRAWING IS TO BE READ IN CONJUNCTION WITH THE ELECTRICAL SPECIFICATIONS.
- E) ALL WORK TO COMPLY WITH RELEVANT STANDARD CODES OF PRACTICE, SPECIFICATIONS AND REGULATIONS.
- F) NOT WITHSTANDING ANYTHING TO THE CONTRARY, ALL RIGHTS RESERVED. NO PART OF THIS DRAWING MAY BE REPRODUCED IN ANY MEDIUM OR BY ELECTRONIC MEANS AND FURTHEREDISTRIBUTION OF THIS DRAWING WITHOUT THE WRITTEN PERMISSION OF THE ORIGINAL USER, WITHOUT THE WRITTEN PERMISSION OF EIVA CONSULTING ENGINEERS

- ## Electrical Notes

TYPICAL ARRANGEMENT OF CORPORATE CONNECTIONS ON DESK

REV	DATE	BY	DESCRIPTION
REVISIONS			

POWERING DEVELOPMENT™

PROJECT/SERVICES

Lighting and Power L

FILE:	LAYERS:
1	1
2	2
3	3
4	4
5	5
6	6
7	7
8	8
9	9
10	10
11	11
12	12
13	13
14	14
15	15
16	16
17	17
18	18
19	19
20	20
21	21
22	22
23	23
24	24
25	25
26	26
27	27
28	28
29	29
30	30
31	31
32	32
33	33
34	34
35	35
36	36
37	37
38	38
39	39
40	40
41	41
42	42
43	43
44	44
45	45
46	46
47	47
48	48
49	49
50	50
51	51
52	52
53	53
54	54
55	55
56	56
57	57
58	58
59	59
60	60
61	61
62	62
63	63
64	64
65	65
66	66
67	67
68	68
69	69
70	70
71	71
72	72
73	73
74	74
75	75
76	76
77	77
78	78
79	79
80	80
81	81
82	82
83	83
84	84
85	85
86	86
87	87
88	88
89	89
90	90
91	91
92	92
93	93
94	94
95	95
96	96
97	97
98	98
99	99
100	100

NOTES: (1) – Contractor to ensure max distance between draw boxes 20 metres notwithstanding anything to contrary

(2) - Draw boxes required after every second 90 deg. bend or 180 deg. total of slow bends

(3) – All unwired conduits to be provided with draw wires. These will be withdrawn and checked at random

(4) – Cast in conduits to be spaced 35mm. minimum

