DOOR SCHEDULE

LOCATION	ABLUTION ENTRANCES	STANDARD ABLUTION CUBICLES	ACCESSIBLE ABLUTION CUBICLES	STORE ROOM	STRONG ROOM / HIGH VALUE STORAGE	FIRE EXIT DOORS
						
NR.	D01	D02	D45	D06	D03	D05
TYPE	MASONITE HONEYCOMB HOLLOW CORE DOOR WITH LOCK SLOT	MASONITE HONEYCOMB HOLLOW CORE DOOR WITH LOCK SLOT	MASONITE SEMI SOLID DOOR WITH LOCK SLOT.	MASONITE HONEYCOMB HOLLOW CORE DOORS WITH LOCK SLOT	CLASS D, BITCOM RUBIDOR FIRE DOOR, CONSTRUCTED FROM A MAGNESIUM OXYCHLORINE MONOLITHIC REINFORCED INSULATIVE MATERIAL. CLADD WITH 2mm CLASS D GALVANIZED MILD STEEL SHEETING ON BOTH SIDES.	CLASS D, BITCOM RUBIDOR FIRE DOOR, CONSTRUCTED FROM A MAGNESIUM OXYCHLORINE MONOLITHIC REINFORCED INSULATIVE MATERIAL. CLADD WITH 2mm CLASS D GALVANIZED MILD STEEL SHEETING ON BOTH SIDES.
FRAME	SET TO FIT EXISING FRAME	SET TO FIT EXISING FRAME IF EXISTING	SET TO FIT EXISING FRAME	(2 X) FLUSH 800mm WIDE x 2066mm HIGH ALLUMINIUM DOUBLE DOOR FRAME WITH 20mm WIDE FRAME EDGE AND DOUBLE REBATE 10MM CLOSER SECTION TO SUIT 90mm THICK DRY-WALLING SYSTEM.CLEAR OPEN SECTION FOR DOOR LEAF = 1600mm WIDE X 2046mm HIGH.	2mm CLASS D GALVANISED MILD SHEET, FORMED TO DOUBLE REBATED PROFILE WITH 52mm x 25 mm REBATES.	2mm CLASS D GALVANISED MILD SHEET, FORMED TO DOUBLE REBATED PROFILE WITH 52mm x 25 mm REBATES.
IRON MONGERY	HINGES:3 X IronWare IW 3040 100 X 44 mm Sinkless Hinge. ESCTCHEON: Ironware - IW Calini 1904-24SS screw type Rose(brushed Stainless Steel) LOCK SET: Dorma D036S Multi Lever Sash Lock. LOUVRE: Only if required by mechanical Engineer. CLOSER KIT: GEZE LINTEL BRACKETSILV (for inwards opening door) GEZE TS4000G DA EN1-6 DELAYED ACTION SLIDE CHANNEL DOOR CLOSER SILV KICK PLATES: 200mm high x2mm thick brushed stainless steel kick plates fitted both sides, 15mm gap around edges to door leaf.	HINGES:3 X IronWare IW 3040 100 X 44 mm Sinkless Hinge. INDICATOR HANDLE LOCK SET: IronWare - IW 1926 (Brushed S/Steel) ESCUTCHEON: Ironware - IW Calini 1904-24SS screw type Rose(brushed Stainless Steel) LOUVRE: Only if required by mechanical Engineer.	HINGES: N/A. part of steel frame Indicator HANDLE SET: IronWare - IW 1926(Brushed S/Steel) LOCK SET: IronWare - IW 2031 Dead Lock. GRAB RAIL: Iron Ware - IW 1306 (back to back through fix to both sides of the door) - fitted horizontally @ 800mm AFFL. REBATE KIT: N/A part of steel frame. CLOSER KIT: GEZE LINTEL BRACKETSILV (for outwards opening door) GEZE TS4000G DA EN1-6 DELAYED ACTION SLIDE CHANNEL DOOR CLOSER SILV KICK PLATES: 200mm high x2mm thick brushed stainless steel kick plates fitted both sides, 15mm gap around edges to door leaf. LOUVRE: Only if required by mechanical Engineer.	HINGES: 3x Iron Ware IW 3040 100 x44mm Sinless Hinge. HANDLE SET: IronWare - IW Calini 1019 through fix Lever Handle (Brushed Stainless Steel) ESCUTCHEON: IronWare - IW Calini 1019 through fix Lever Handle (Brushed Stainless steel) LOCKSET:Dorma Dorma D036S Multi Lever Sash Lock. IW dust excluding socket. IW4023 150mm flush lever bolt. DOOR STOP: 2x IronWare - IW 5000 Cylibndrical door stop (SS)	SECURITY HARDWARE HINGES: 6 x Heavy duty thick flanged brass hinges with nylon washers.Standard door leaves are fitted with 2 pair of hinges . PULL HANDLE: Stainless Steel pull handle LOCKSET: Heavy Duty Lock DOOR STOP: 2x IronWare - IW 5000 Cylibndrical door stop (SS) OTHER: Floor Bolt	SECURITY HARDWARE HINGES: 6 x Heavy duty thick flanged brass hinges with nylon washers.Standard door leaves are fitted with 2 pair of hinges . LOCKSET: DETEX V40 Series Heavy duty emergency exit device. Heavy duty 20mm Staninless Steel deadlocking latch.
DOOR	MASONITE HONEYCOMB HOLLOW CORE DOOR WITH LOCK SLOT, Painted WP03.	MASONITE HONEYCOMB HOLLOW CORE DOOR WITH LOCK SLOT, Painted WP03.	FLUSH 945mm x 2032mm HIGH MASONITE FINISHED SEMI-SOLID DOOR WITH LOCK SLOT . painted WP03	2X FLUSH 800mm wide x 2032mm HIGH MASONITE HONEYCOMB HOLLOW CORE DOORS WITH SASH SLOTAND INLINE BARREL BOLTS TOP AND BOTTOM. painted WP03.	1511wide x 2032 high, CLASS D, BITCOM RUBIDOR FIRE DOOR, CONSTRUCTED FROM A MAGNESIUM OXYCHLORINE MONOLITHIC REINFORCED INSULATIVE MATERIAL WITH EXCELLENT FIRE RESISTANCE AND MECHANICAL STRENGTH,finished with standard steel clad or vaneered with concealed steel cladding.	1511wide x 2032 high, CLASS D, BITCOM RUBIDOR FIRE DOOR, CONSTRUCTED FROM A MAGNESIUM OXYCHLORINE MONOLITHIC REINFORCED INSULATIVE MATERIAL WITH EXCELLENT FIRE RESISTANCE AND MECHANICAL STRENGTH,finished with standard steel clad or vaneered with concealed steel cladding.
QTY	3	4	1	1	3	7

WINDOW SCHEDULE

DRAWING		
NR.	W01	W02
AREA		
TYPE	ALUMINIUM FRAME WINDOW	50x50mm STEEL FRAME
GLASS	CLEAR GLASS	GALVANISED SHEETING
VALUE	U: 0.0 SHGc: 0.00	
QTY	1	1

BURGLAR BAR DETAIL

Burglar bars formed by 15,88 x 15.88 x 0.9mm Cold rolled steel square tubing frame with 8mm Solid round steel horizontal bars welded on.
Frame to fit to inside of window opening to inside of building.
All opening sizes to be checked on site before manufacture.

DRAWING		
NR.	BB01	BB02
QTY	4	16

Burglar Proofing Schedule
1:50

CASHIER'S OFFICE	AUCTION VIEWING ROOM DOOR
	
D41	D06
MASONITE SEMI-SOLID DOORS WITH LOCK SLOT	MASONITE HONEYCOMB HOLLOW CORE DOORS WITH LOCK SLOT
855 mm wide x 2066 mm HIGH ALUIMINIUM DOOR FRAME WITH 20mm WIDE FRAME EDGE AND 10mm CLOSER SECTION TO SUIT 90mm THICK DRY WALLING SYSTEM, CLEAR OPEN SECTION FOR DOOR LEAF = 815mm WIDE 2046 HIGH.	(2 X) FLUSH 800mm WIDE x 2066mm HIGH ALLUMINIUM DOUBLE DOOR FRAME WITH 20mm WIDE FRAME EDGE AND DOUBLE REBATE 10MM CLOSER SECTION TO SUIT 90mm THICK DRY-WALLING SYSTEM.CLEAR OPEN SECTION FOR DOOR LEAF = 1600mm WIDE X 2046mm HIGH.
SECURITY HARDWARE HINGES: 3 x Iron Ware IW 3040 100 X 44 mm sinless Hinge. HANDLE SET: Iron Ware IW - cALINI 1019 through fix SS Lever Handle. Escusheon: Iron Ware - IW Calinio 1904 - 0555 screw TYPE 55 rose. LOCKSET: Dorma D036S eURA Profile cylinder sash lock. Dorma DDC056501 65mm Eura Profile double cylinder. DOOR STOP: Iron Ware - IW 5000 Cylindrical door stop.	SECURITY HARDWARE HINGES: 6 x Heavy duty thick flanged brass hinges with nylon washers.Standard door leaves are fitted with 2 pair of hinges . LOCKSET: DETEX V40 Series Heavy duty emergency exit device. Heavy duty 20mm Staninless Steel deadlocking latch.
2X FLUSH 800mm wide x 2032mm HIGH MASONITE HONEYCOMB HOLLOW CORE DOORS WITH SASH SLOTAND INLINE BARREL BOLTS TOP AND BOTTOM. painted WP03.	2X FLUSH 800mm wide x 2032mm HIGH MASONITE HONEYCOMB HOLLOW CORE DOORS WITH SASH SLOTAND INLINE BARREL BOLTS TOP AND BOTTOM. painted WP03.
1	1

REVISIONS

Date	Description	Drawn by

SIGNED ..... ARCHITECT: SACAP NUMBER:

SIGNED ..... OWNER

COPYRIGHT IS RESERVED BY THE ARCHITECT

SERVICE MOSEBETSI DIENS

TENDER DOCUMENTATION
ADDITIONS AND ALTERATIONS TO WAREHOUSE FOR SARS MUSINA.

NOT FOR CONSTRUCTION

DRAWING DESCRIPTION: DOORS & WINDOWS
HO NGOLA / HO BOLEDISA
TEKENING / BESKRYWING

	NAME LEBITSO NAAM	DATE LETSATSI DATUM
DESIGNED HO NGOLA PLANE ONTWERP		
DRAWN NGODILWE GETEKEN		
CHECKED BY: HLAHLOBILWE KE: NAGEGAAN DEUR:		
SCALE : SEKALA : SKAAL :	1:50 @ A1	
APPROVED : HO DUMELANA : GOEDGEKEUR :		
FILE NR : PEHO YA NOMORO : LEER NO :	AMS_LP_055_SM_W	
DRWG. NR : NGODISO YA NOMORO : TEK. NO :	AMS_LP_055_SM_W_TD_D-S	REVISION NR : PHETOHO : HERSIENING NO: