

## REMKOR PUBLIC BENCH SEAT

Last Revised: 24-08-2015

**Code: CHAIR-30-PB-X** (where X indicates number of seats)



### CODE Description

<b>CHAIR</b>	<b>30</b>	<b>PB</b>	<b>X</b>
CATEGORY	CATALOG NO	PUBLIC BENCH	NO. OF SEATS

### Barcode:

SARS to apply barcode - not vendor.

Remkor Standard Range.  
NO arm rests to be fitted.

2 Seater: CHAIR-30-PB-2

3 Seater: CHAIR-30-PB-3

4 Seater: CHAIR-30-PB-4

## TECHNICAL DATA

<b>Seat &amp; Back:</b>	500mm wide perforated brushed stainless steel seat & back, ergonomically curved for comfort. Top, bottom and edges machine bent for safety and neatness of finish. 650mm centre to centre offset for seat spacing.
<b>Frame &amp; Leg:</b>	Leg lazer cut from 10mm steel with footplate - design to match picture - with SARS approval. No moulded or hollow sections. Finish to be mild steel iron phosphated, epoxy coated min 80 micron "aluclear" silver-grey. Each seat to support a minimum weight of 130kg. Frame to support 130kg multiplied by the number of seats (X).
<b>Design:</b>	Back rest and seat support frame same as for leg (see above), but from 8mm steel and bent and tucked for neatness. Beam mounted seating system. Free standing (not mounted to floor). Beam to be rectangular and from 3mm thick section. All components welded and bolted together (allen key size to manufacturer). Isolating grommets to avoid contact between mild steel and stainless steel. Ensure item including feet robust and acceptable for high traffic. Sample to be approved by SARS Facilities before ordering. High strength plastic feet on adjustable 12mm thread bolt.
<b>Supplier: Warranty &amp; Design:</b>	Remkor Product. Plasticised sticker by supplier fixed under seat frame stating: Supplier, physical address and contact details. Unit to be supplied with MINIMUM 5 year Supplier Warranty under high ware and tear public conditions. The specifications as contained in this document are the minimum SARS requirements. Supplier/Vendor to note Remkor product as designed without modification.