



- General Notes:
- Slurry sealing shall be performed as a surface treatment to extend the life and enhance the appearance of the existing pavement.
 - The slurry sealing work shall comply with local, regional, and national standards and specifications for slurry seal applications.
 - Prior to slurry sealing, the pavement surface shall be cleaned of all debris, loose material, and vegetation.

LEGEND

 ANIONIC STABLE MIX GRADE 60% BITUMEN EMULSION SLURRY SEAL APPLIED BY HAND

 JOINTS TO BE REPLACED WITH 50MM EPOXY THERMAPEX WATER TIGHT DECK EXPANSION JOINT SYSTEM

COPYRIGHT

In accordance with the relevant clauses of the Copyright Act (Act 98 of 1978) relating to assignment, all documents prepared by Celankobe in connection with the project remain the property and copyright of Celankobe, subject to their use by the client for the particular project to which this document relates, and the client shall not be entitled, either directly or indirectly, to make use of the document(s) for any additional or similar works or publish the same except with the prior consent from Celankobe.

CIVIL AND STRUCTURAL



TEL : +27 871 520 083
CENTURIA PARK 265, VON WILlich, DIE HOUWES, CENTURION

PROJECT TITLE :
LEHAE LA SARS REHABILITATION

CLIENT :
SOUTH AFRICAN REVENUE SERVICE

DRAWING TITLE:
SKEMATIC EXISTING DRAINS

DRAWN BY : N. MOTSA **DATE :** 18/07/2023
CHECKED BY : L. DLAMINI **DATE :**
SCALE : 1:100 **RESPONSIBLE PROFESSIONAL :** L. DLAMINI

REVISIONS:		
No.	Date	Description
01	27/02	
SIZE A0		
DRAWING NUMBER 001/CIV/DL/2023		REVISION 00