



General Notes:
1. Asphalt resurfacing shall be performed to restore the pavement surface and enhance its structural integrity.
2. The resurfacing work shall comply with local, regional, and national standards and specifications for asphalt paving.
3. Prior to resurfacing, the existing pavement shall be thoroughly cleaned of all debris, oil stains, and vegetation.

LEGEND

-  CONTINUOUSLY GRADED SURFACING COURSE: 50/50 PENETRATION GRADE BITUMEN ASPHALT SURFACING (25mm THICK) TO BE APPLIED IN 2 LAYERS
-  JOINTS TO BE REPLACED WITH 50MM BASALT THERMAPEX WATER TIGHT DECK EXPANSION JOINT SYSTEM

COPYRIGHT

In accordance with the relevant clauses of the Copyright Act (Act 98 of 1978) relating to assignment, all documents prepared by Celankobe in connection with the project remain the property and copyright of Celankobe, subject to their use by the client for the particular project to which this document relates, and the client shall not be entitled, either directly or indirectly, to make use of the document(s) for any additional or similar works or publish the same except with the prior consent from Celankobe.

CIVIL AND STRUCTURAL



TEL : +27 871 520 083
CENTURIA PARK 265, VON WILlich, DIE HOUWES, CENTURION

PROJECT TITLE :

LEHAE LA SARS REHABILITATION

CLIENT :

SOUTH AFRICAN REVENUE SERVICE

DRAWING TITLE:

SKEMATIC PARKING LOT 1

DRAWN BY : N. MOTSA DATE : 18/07/2023
CHECKED BY : L. DLAMINI DATE :
SCALE : N.T.S
RESPONSIBLE PROFESSIONAL: L. DLAMINI

REVISIONS:

No.	Date	Description	Int.
01	27/02		

SIZE	DRAWING NUMBER	REVISION
A0	001/CIV/P1/2023	00